

**PRODUCT DESCRIPTION**

THE **THERMOTEC BT05** IS A HOT MELT ADHESIVE OF PREMIUM QUALITY AVAILABLE IN TRANSPARENT STICKS. IT PROVIDES AN EXCELLENT ADHESION TO A WIDE VARIETY OF MATERIALS.

**TECHNICAL DATA**

<b>TYPE :</b>	ETHYL-VINYL ACETYL (EVA) CO-POLYMER
<b>COLOUR :</b>	TRANSPARENT
<b>ODOUR :</b>	SLIGHT RESIN ODOUR
<b>APPEARANCE :</b>	STICKS
<b>SOFT POINT :</b>	80°C (176°F)
<b>TOXICITY :</b>	NO HAZARDOUS INGREDIENTS
<b>VISCOSITY :</b>	12 000 CPS @ 180°C(356° F)
<b>SPECIFIC GRAVITY:</b>	0,98
<b>MAXIMUM OPEN TIME :</b>	5-8 SECONDS
<b>SETTING TIME :</b>	VARIABLE
<b>WORKING TEMPERATURE :</b>	150-160°C (302-320°F)
<b>DIAMETER :</b>	11,2MM (0,44")
<b>COVERAGE :</b>	NOT AVAILABLE
<b>STORAGE :</b>	STORE IN CLOSED CONTAINER IN A DRY PLACE. AVOID DIRECT CONTACT WITH THE HEAT AND LIGHT. USE THE OLDEST MATERIAL FIRST (FIFO). KEEP OUT OF CHILDREN REACH.

**CARACTERISTICS**

- EXCELLENT ADHESION TO WOODS, CERAMICS, PLASTICS, TEXTILES, LEATHERS, PAPERS, PAPERBOARDS AND LIGHT METAL
- STRONG ADHESION BUT STILL OFFERS A FLEXIBLE JOINT
- EXCELLENT FLOW

**TYPICAL APPLICATION**

THIS ADHESIVE IS RECOMMENDED IN PRODUCTION TO ASSEMBLE WOODS, CERAMICS, PLASTICS, TEXTILES, LEATHERS, PAPERS, PAPERBOARDS AND LIGHT METALS.

**IMPORTANT NOTICE**

ALL STATEMENTS, RECOMMENDATIONS AND TECHNICAL INFORMATION CONTAINED IN THIS DOCUMENT ARE BASED ON TESTS AND INFORMATION WHICH TEC-N-TEC BELIEVES TO BE ACCURATE AS OF THIS DATE. THE BUYERS HOWEVER SHOULD TEST THIS PRODUCT BEFORE USE. TEC-N-TEC WILL ASSUME NO OBLIGATION OR LIABILITY FOR RESULTS OBTAINED FROM THE USE OF THIS PRODUCT.

THE PRODUCT AND INFORMATION HEREIN ARE BELIEVES TO BE TRUE. TEC-N-TEC INC. WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT CONSEQUENTIAL ECONOMIC OR ANY OTHER DAMAGE WHATSOEVER, EXCEPT TO REPLACE THE PRODUCT AND OR REFUND THE PURCHASE PRICE TO THE PURCHASER.

**TEC-N-TEC INC.**

8244 PASCAL-GAGNON  
MONTREAL, QC H1P 1Y4

TEL : (888)832-7777 - (514)325-7777  
FAX : (888)832-0282 - (514)325-0282

WEBSITE : WWW.TEC-N-TEC.COM  
EMAIL : PRO@TEC-N-TEC.COM