



PRODUCT DESCRIPTION

THE ADHERTEC 1795 TAPE IS A SOLVENT FREE PRE-MADE RESIN RUBBER PRESSURE SENSITIVE TAPE. ON REEL, THE TAPE IS UNROLLED EASILY, BECAUSE IT IS ROLLED WITH A PAPER LINING TREATED WITH A SILICONE OF HIGH QUALITY. THIS TAPE OFFERS A SUPERIOR ADHESION TO PLASTICS, METALS, TEXTILES AND POLYETHYLENE SHEETING.

TECHNICAL DATA

TYPE :	RUBBER RESIN TAPE
COLOUR :	CLEAR TO LIGHT YELLOW
TOTAL THICKNESS :	1/32" (0.8MM) OR 1/64" (0.4MM)
ADHESIVE THICKNESS :	NOT AVAILABLE
PEEL RESISTANCE :	NOT AVAILABLE
SHEAR RESISTANCE :	NOT AVAILABLE
U.V. RESISTANCE :	NO
CHEMICAL RESISTANCE :	NO
APPLICATION TEMPERATURE :	> 10°C (50°F)
HEAT RESISTANCE :	40°C (104°F)
COLD RESISTANCE :	0°C (32°F)
DENSITY :	NOT AVAILABLE
SHelf LIFE :	2 YEARS BETWEEN 5°C (41°F) AND 25°C (77°F)
STORAGE :	STORE IN CLOSED CONTAINER IN A DRY PLACE. AVOID DIRECT CONTACT WITH THE HEAT AND LIGHT. USE THE OLDEST MATERIAL FIRST (FIFO). KEEP OUT OF CHILDREN REACH.

CARACTERISTICS

- CLEAN AND EASY ALTERNATIVE TO ADHESIVES
- AGGRESSIVE RUBBER RESIN ADHESIVE
- PERMANENTLY FLEXIBLE
- OFFERED IN ROLLS OF 66 YARDS (60 METERS) LONG, ROLLED ON A 3" (75MM) CORE
- AVAILABLE IN WIDTH OF 1/2" (12.7MM), 3/4" (19MM), 1" (25.4MM), 1 1/2" (38MM) AND 2 1/4" (57MM)

APPLICATION METHOD

THIS TAPE IS APPLY DIRECTLY TO THE SURFACE TO BE GLUED. ALL SURFACES MUST BE CLEAN, DRY, WITHOUT DUST AND FAT FREE.

IMPORTANT NOTICE

ALL STATEMENTS, RECOMMENDATIONS AND TECHNICAL INFORMATION CONTAINED IN THIS DOCUMENT ARE BASED ON TESTS AND INFORMATION WHICH TEC-N-TEC BELIEVES TO BE ACCURATE AS OF THIS DATE. THE BUYERS HOWEVER SHOULD TEST THIS PRODUCT BEFORE USE. TEC-N-TEC WILL ASSUME NO OBLIGATION OR LIABILITY FOR RESULTS OBTAINED FROM THE USE OF THIS PRODUCT.

THE PRODUCT AND INFORMATION HEREIN ARE BELIEVES TO BE TRUE. TEC-N-TEC INC. WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT CONSEQUENTIAL ECONOMIC OR ANY OTHER DAMAGE WHATSOEVER, EXCEPT TO REPLACE THE PRODUCT AND OR REFUND THE PURCHASE PRICE TO THE PURCHASER.



TEC-N-TEC INC.

8244 PASCAL-GAGNON
MONTREAL, QC H1P 1Y4

TEL : (888)832-7777 - (514)325-7777
FAX : (888)832-0282 - (514)325-0282

WEBSITE : WWW.TEC-N-TEC.COM
EMAIL : PRO@TEC-N-TEC.COM