

PRODUCT DESCRIPTION

THE **THERMOTEC GKP15** IS A PREMIUM AMBER THERMOSETTING ADHESIVE IN STICK. IT OFFERS A HIGH STRENGTH ON A VARIETY OF MATERIALS AND IS DESIGNED FOR SEALING CRATES AND CARDBOARD BOXES. THIS ADHESIVE IS APPROVED FOR USE IN FOOD PROCESSING ESTABLISHMENTS PROVIDED THAT IT IS APPLIED TO THE OUTER SURFACE OF PACKAGING MATERIALS.

TECHNICAL DATA

TYPE :	ETHYL-VINYL ACETYL (EVA) CO-POLYMER
COLOUR :	AMBER
ODOUR :	SLIGHT RESIN ODOUR
APPERANCE :	STICKS
SOFT POINT :	99°C-119°C(210°F-246°F)
TOXICITY :	NO HAZARDOUS INGREDIENTS
VISCOSITY :	2 700 CPS to 4 700 CPS @ 177°C(350° F)
SPECIFIC GRAVITY:	-
MAXIMUM OPEN TIME :	45 SECONDS
SETTING TIME :	VARIABLE (< 5 seconds)
WORKING TEMPERATURE :	160-200°C (320-392°F)
DIAMETER :	11,2MM (0,44")
COVERAGE :	NOT AVAILABLE
STORAGE :	STORE IN CLOSED CONTAINER IN A DRY PLACE. AVOID DIRECT CONTACT WITH THE HEAT AND LIGHT. USE THE OLDEST MATERIAL FIRST (FIFO). KEEP OUT OF CHILDREN REACH.

CARACTERISTICS

- EXCELLENT ADHESION ON MANY PACKAGING MATERIALS
- STRONG BUT FLEXIBLE BONDING PLAN
- HIGH RESISTANCE TO HEAT AND COLD
- EXCELLENT SPREAD PROPERTY

TYPICAL APPLICATION

THIS ADHESIVE IS RECOMMANDED FOR ASSEMBLY, PACKAGING, STORE DISPLAY AND ASSEMBLY WORK,

IMPORTANT NOTICE

ALL STATEMENTS, RECOMMENDATIONS AND TECHNICAL INFORMATION CONTAINED IN THIS DOCUMENT ARE BASED ON TESTS AND INFORMATION WHICH TEC-N-TEC BELIEVES TO BE ACCURATE AS OF THIS DATE. THE BUYERS HOWEVER SHOULD TEST THIS PRODUCT BEFORE USE. TEC-N-TEC WILL ASSUME NO OBLIGATION OR LIABILITY FOR RESULTS OBTAINED FROM THE USE OF THIS PRODUCT.

THE PRODUCT AND INFORMATION HEREIN ARE BELIEVES TO BE TRUE. TEC-N-TEC INC. WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT CONSEQUENTIAL ECONOMIC OR ANY OTHER DAMAGE WHATSOEVER, EXCEPT TO REPLACE THE PRODUCT AND OR REFUND THE PURCHASE PRICE TO THE PURCHASER.

**TEC-N-TEC INC.**8244 PASCAL-GAGNON
MONTREAL, QC H1P 1Y4TEL : (888)832-7777 - (514)325-7777
FAX : (888)832-0282 - (514)325-0282**Revision 1 : 11-15-2023**WEBSITE : WWW.TEC-N-TEC.COM
EMAIL : PRO@TEC-N-TEC.COM